

Features

- Vitreous china.
- Elongated bowl.
- Equipped with Sloan FLUSHMATE®– Sloan® Valve Company.
- Polished chrome trip lever.
- Tank cover locks
- Less seat and supply.
- 12" (305 mm) rough-in.
- 1.0 gpf (3.8 lpf).
- 11-1/2" (292 mm) x 9-1/2" (241 mm) water area.
- 30-3/8" (772 mm) x 21-1/4" (540 mm) x 29-3/4" (756 mm).

Recommended Products/Accessories

K-4636 Cachet® Quiet-Close™ Elongated Toilet Seat K-5588 Purefresh® Elongated Toilet Seat K-4108 C³®-230 elongated cleansing toilet seat K-5420 Low-Profile Bolt Caps

Included Components

Product consists of: K-4303 Toilet Bowl K-4484-TR Toilet Tank Additional Components: Bolt cap accessory pack Equipped with Sloan FLUSHMATE® – Sloan® Valve Company Tank cover Trip lever





Codes/Standards ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 199

DOE - Energy Policy Act 1992 EPA WaterSense[®] California Energy Commission (CEC)

KOHLER[®] One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

0	White
96	Biscuit

7 Black Black™



Wellworth[®] Classic


Pressure Lite[®] Toilet K-3531-TR



Wellworth® Classic

Pressure Lite® Toilet

K-3531-TR



Technical Information

All product dimensions	s are nominal.
Toilet type:	Two-piece, Floor-mount
Waste Outlet:	Floor
Bowl shape:	Elongated
Flush type:	Pressure Assisted
Trap passageway:	2-1/4" (57 mm)
Water Consumption	
Full:	1 gpf (3.8 lpf)
Water surface size:	11-1/2" x 9-1/2" (292 mm x 241 mm)
Rim to water surface:	5-5/8" (143 mm)
Rough-in:	12" (305 mm)
Seat-mounting holes:	5-1/2" (140 mm)

Install this product according to the installation instructions.

Notes

For back-to-back toilet installations: Use only a 45° double wye fitting.

Fixture Supply Requirements

Min static pressure:	35 psi (241.3 kPa)
Max static pressure:	80 psi (551.6 kPa)

