# **KOHLER**<sub>®</sub>

77" H sliding shower door with 3/8"-thick glass K-709079-10L

#### Features

- Frameless design emphasizes glass and creates a sleek, minimalist look
- Vertical handle with inside knob on moving panel
- Tempered glass ensures enhanced safety and durability
- CleanCoat®+ glass coating creates a hydrophobic barrier that repels water, soap scum, and residue, saving time and protecting shower doors 10 times longer than original CleanCoat. (Based on 2021 internal wear/abrasion testing using a microfiber cloth.)
- Smooth, easy-to-clean wall jambs
- SealNetik<sup>™</sup> full-length magnetic seal keeps door firmly closed, providing excellent water containment
- Shower door configuration consists of one sliding panel and one stationary panel
- Coordinates with other products in the Rely collection

#### Material

- Frameless, 3/8" (10 mm) thick Crystal Clear tempered glass
- Anodized aluminum prevents rust and corrosion

#### Installation

- Fits opening widths 56-5/8" 59-5/8" (1438 –1514 mm)
- 77" (1956 mm) high, with a lofty 73-7/8" (1876 mm) minimum head clearance
- 3" (76.2 mm) width adjustment
- Out-of-plumb adjustability simplifies installation
- Door can be installed to open to the left or right to suit your bathroom layout
- For residential and hospitality use



### **Codes/Standards**

ANSI Z97.1 CAN/CGSB-12.1 CPSC 16CFR 1201

## KOHLER® One-Year Limited

#### Warranty

See website for detailed warranty information.

#### **Available Colors/Finishes**

Color tiles intended for reference only.

#### Color Code Description

SHP	Bright Polished Silver
2MB	Vibrant® Brushed Moderne Brass
BNK	Anodized Brushed Nickel
BL	Matte Black


#### Available Glass Options Code Description

L Crystal Clear

1-800-4KOHLER (1-800-456-4537) Kohler Co. reserves the right to make revisions without notice to product specifications. For the most current Specification Sheet, go to <u>www.kohler.com</u>. 10-21-2023 21:07 - US/CA/LM

# **KOHLER**

### Rely® 77" H sliding shower door with 3/8"-thick glass K-709079-10L



All product dimensions are nominal. Base-To-Wall 1/2" (13 mm) Radius - Max:

The vertical opening should be a minimum of 78-1/2" (1994 mm) to allow for installation clearance.

