# For Commercial and Institutional Applications

Job Name \_

Job Location

Engineer \_\_\_

Approval \_\_\_\_

Contractor \_\_\_\_

Approval \_\_\_\_\_

Contractor's P.O. No.

Representative \_\_\_\_

# ANKA<sup>®</sup> QL Series Hose Quick-Lock Couplings

Sizes: 3/4" - 11/2" (20 - 40mm)

These quick-lock couplings are made from high grade glass fiber reinforced nylon. These quick-action couplings are designed to be put together and taken apart in one easy twist action. Because the seal ring end is a consistent size, each coupling is interchangeable, allowing a wide range of configurations. Quick-lock couplings are used in farming, irrigation, and industry applications.

## Features

- Quick and easy to use.
- Connect or take apart with one easy twisting motion.

### Applications

- Pumping
- Marine
- Wash down

#### Materials

Body:Glass fiber reinforced nylonSeal:AlcrynThreads:NPT Threads

#### Maximum Working Pressure:

150 psi – 1000 kpa (10 bar) @ 68°F (20° C)

#### NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (978) 689-6066 • F: (978) 975-8350 • Watts.com Canada: T: (905) 332-4090 • F: (905) 332-7068 • Watts.ca Latin America: T: (52) 81-1001-8600 • Watts.com



#### Models- Range 34" - 11/2"