For Commercial & Residential Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

EAD FREE

Series LFWAMV

Brass Angle Meter Valves

Sizes: 3/4" x 1" (20 x 25mm)

Series LFWAMV Lead Free* cast copper silicon alloy Angle Meter Valves are designed for residential and light commercial incoming water supply service. The LFWAMV features Lead Free* construction to comply with Lead Free* installation requirements.

Features

- Cast Lead Free* cast copper silicon alloy
- Available with or without waste feature
- Angle pattern models

Models

LFWAMV

3/4" (20mm) flare x 3/4" (20mm) female IPS connections or 3/4" (20mm) flare x 1" (25mm)

female IPS connections


LFWAMV-W

3/4" (20mm) flare 3/4" (20mm) female IPS connections with waste feature or 1" (25mm) flare x 3/4" (20mm) female IPS connections with

waste feature

Pressure - Temperature

Maximum Pressure: 125psi (9 bar)





LFWAMV

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Inquire with governing authorities for local installation requirements

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Dimensions - Weights

MODEL	SIZE (D	N)	DIMENSIONS									WE	WEIGHT	
			Α		В		B1		D		K			•
	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kgs
LFWAMV	34 FL x 34 IPS	20 x 20	3/4 FL	20	61//8	156	65/8	168	3	76	2 5⁄16	58	1.2	0.94
LFWAMV	1 FL x ¾ IPS	25 x 20	1 FL	25	61//8	156	65%	168	3	76	2 ⁵ / ₁₆	58	1.2	0.94
LFWAMV-W	34 FL x 34 IPS	20 x 20	3/4 FL	20	61//8	156	65/8	168	3	76	2 5⁄16	58	1.2	0.94
LFWAMV-W	1 FL x ¾ IPS	25 x 20	1 FL	25	61//8	156	65/8	168	3	76	2 5⁄16	58	1.2	0.94

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

USA: T: (978) 689-6066 • F: (978) 975-8350 • Watts.com Canada: T: (905) 332-4090 • F: (905) 332-7068 • Watts.ca Latin America: T: (52) 81-1001-8600 • Watts.com

ES-LFWAMV 1323 © 2013 Watts