

Occasion™ Single-function 1.75 gpm handshower K-27052-G

### Features

- Single-function handshower delivers a full, consistent spray, regardless of water pressure.
- Full Coverage with Katalyst technology delivers a drenching spray experience, ideal for rinsing shampoo from hair.
- MasterClean<sup>™</sup> sprayface features an easy-to-clean surface that withstands mineral buildup.
- Optimized sprayface for maximum performance.
- 1.75 gpm (6.6 lpm) maximum flow rate at 80 psi (5.5 bar).
- Part of the Occasion bathroom faucet and accessory collection.

### Material

- Premium material construction for durability and reliability.
- KOHLER finishes resist corrosion and tarnishing.

### Technology

• Katalyst<sup>®</sup> air-induction technology infuses water with air, creating bigger drops for a more powerful spray.

### Installation

- G 1/2 inlet and outlet.
- Requires shower hose (sold separately).
- Bracket or slidebar required for wall-mount installation.
- Deck-mount holder required for deck-mount installation.

### Water Conservation & Rebates

 This product can help a building earn Water Efficiency points in LEED<sup>®</sup> Green Building Rating System.

### **Recommended Products/Accessories**

K-9514 60" Shower Hose K-8593 72" Shower Hose K-26309 Wall-mount handshower holder K-26310 Wall-mount handshower holder with supply elbow and check valve K-26312 32-1/8" slidebar K-26313 40" slidebar K-26314 31-1/2" slidebar with integrated water supply K-23723 Faucet cleaner





### **Codes/Standards**

ASME A112.18.1/CSA B125.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC)

## KOHLER<sup>®</sup> Faucet Lifetime Limited Warranty

See website for detailed warranty information.



# KOHLER, Faucets

### Occasion™ Single-function 1.75 gpm handshower K-27052-G





### **Technical Information**

All product dimensions are nominal.

### Handshower:

Rated maximum<br/>flow:1.75 gal/min (6.6 l/min)<br/>80 psi (5.5 bar)

#### Notes

For use with automatic compensating valves rated at 1.75 gal/min (6.6 l/min) or less.

