



SYMMONS® Safetymix®
the smart choice™

Symmons Safetymix®, the Original

70 years ago, Symmons developed and patented the first fully Pressure-Balancing, single handle shower mixing valve.

It's always been our standard that where safety is concerned, there is no second best. Symmons Safetymix® Pressure-Balancing mixing valves are designed and built to last the life of the building. So if your next project requires a rugged, durable valve to withstand the rigors of a high use commercial or institutional project, think Symmons, think Safetymix.



Symmons Safetymix®
is available in
this finish:



Polished
Chrome



1-100

Safetymix Shower Unit, 4-500
3-port valve, 4-231 showerhead, 300
arm and flange.
4-500 Valve only



1-215-X

Safetymix Tub/Shower Unit, 4-500X
4-port valve, 050 diverter spout, 4-231
showerhead, 300 arm and flange.



1-25-FSB

Safetymix Shower Unit with Open
Flow Hand Shower, 4-500 3-port
valve, FSB hand spray with
30° adjusting bar.



1-50-FSB

Safetymix Tub/Shower Unit with Open Flow
Hand Shower, 4-500 3-port valve, 4-45B lever
diverter, 060 tub spout, FSB hand shower,
with 30° adjusting bar.



1-117-FS

Safetymix Shower Unit with Open Flow
Hand Shower, 4-500 3-port valve, 4-45B
lever diverter, FS hand shower, 4-231
showerhead, 300 arm and flange.



1-217-X-FS

Safetymix Tub/Shower Unit with Open
Flow Hand Shower, 4-500 3-port valve,
4-460 lever diverter, 060 tub spout,
FS hand shower, 4-231 showerhead,
300 arm and flange.

Modifications: Suffix X: Integral service stops - allows water shutoff at valve • Suffix BX: Back inlet and outlet connections, integral stops
• Suffix X-REV: Reverse coring, hot on right, cold on left, for back to back installations with integral stops only • Suffix 3/4: 3/4" valve to increase flow
approximately 20% • Suffix L: Lucite handle in place of lever handle • Suffix FSB: Use in lieu of suffix FS is 30° adjusting bar is desired in place of
hooks on hand shower units • Suffix B-4B: 4B" adjusting bar in place of 30° bar on hand shower units • Suffix VB: Elevated vacuum breaker in place of
in-line vacuum breaker • Suffix QD: Quick disconnect on hand shower units • Suffix 6: 6' hose in place of 5' hose • Suffix R: Vinyl hose in place of
metal on hand shower units • Suffix A: Anchor plates for valve and head • Suffix E: External volume control on head

